

Application No.: 10/047,141

Docket No. BCS03401/PD05970AM

**AMENDMENTS TO THE CLAIMS**

Cancel claims 2, 13-15 and 25-52.

Amend the remaining pending claims as follows:

1. (presently amended) A communications system comprising:

a communication distribution network;

a plurality of communication cable access units, each coupled to the communication distribution network, and to a at least one of the cable access units each receiving power from a respective power supply powered by a main power source, wherein the said power supply includes including a backup battery power source adapted to supply backup power to the an associated communication cable access unit when the main power source fails, and wherein the said power supply further adapted to generate a status information signal indicating on the backup power source, at least one of i) the presence of backup battery, and ii) the power status of the backup battery when power fails, and wherein the communication cable access unit is units adapted to responsively transmit information indicative of monitor the status information signal via the generated by said respective power supply and to check and record the capability of the communication distribution network cable access unit to acquire said status information;

an operator unit coupled via the communication distribution to said network, said operator unit adapted to monitor, for to at least one of the plurality of communication cable access units, and adapted to request and receive from the capability of the communication cable access unit information indicative of the to check and record said status information signal generated by the coupled power supply and also the backup power source status information via two way communication with said cable access unit;

a processor unit coupled to the operator unit, the processor being adapted to receive and access the communication cable access unit information indicative of the to status information signal generated by the coupled power supply; and

a user interface display, responsive to the processor, coupled to said operator unit, and said operator unit adapted to provide display an indication of the respective battery monitored status information for an associated communication cable access unit on said user interface.

Application No.: 10/047,141

Docket No. BCS03401/PD05970AM

2. (presently cancelled) A system as claimed in claim 1, wherein the power supply is further adapted to generate said status information on the backup power source wherein said status information generated is selected from at least one of backup power source on information, backup power source missing information, and backup power source needing replacement information.

3. (presently amended) A system as claimed in claim 1 2, wherein said operator unit is further adapted to generate an alarm message, including an identification of the associated communication cable access unit, on the user interface when status information on the backup power source is received from said associated communication cable access unit indicating a backup power source on condition detected at the monitored communication cable access unit.

4. (presently amended) A system as claimed in claim 1 2, wherein said operator unit is further adapted to generate an alarm message, including an identification of the associated communication cable access unit, on the user interface when status information on the backup power source is received from said associated communication cable access unit indicating at least one of a backup power source on, a backup power source missing, and a backup power source needing replacement condition detected at the monitored communication cable access unit

5. (presently amended) A system as claimed in claim 4, wherein the operator unit is further adapted to monitor backup power source status information from a plurality of communication cable access units located at respective different subscriber premises.

6. (presently amended) A system as claimed in claim 5, wherein the operator unit is further adapted to maintain at least a partial count of the number of communication cable access units respectively reporting a backup power source on condition within a predetermined service area.

7. (presently amended) A system as claimed in claim 6, wherein the operator unit is further adapted to display on the user interface a generalized indication of a service area wide warning condition in lieu of individualized indications for each communication cable access unit when the count of the number of communication cable access units reporting a backup power source on condition exceeds a predetermined value.

8. (as originally filed) A system as claimed in claim 4, wherein said backup power supply is a secondary alternating current power feed.

Application No.: 10/047,141

Docket No. BCS03401/PD05970AM

9. (as originally filed) A system as claimed in claim 4, wherein said backup power supply is a generator.
10. (as originally filed) A system as claimed in claim 4, wherein said backup power supply is a fuel cell.
11. (as originally filed) A system as claimed in claim 4, wherein said backup power supply is a solar cell.
12. (as originally filed) A system as claimed in claim 4, wherein said backup power supply is a battery.
13. (presently cancelled) A system as claimed in claim 1, wherein the cable access unit further comprises a hardware unit adapted to detect the status information from the power supply, and a processor unit adapted to check whether the cable access unit can acquire the backup power source status information and to receive the status information from the hardware unit when acquired and also report said status information back to said operator unit via said network responsive to a request from said operator unit for such status information when received at the cable access unit.
14. (presently cancelled) A system as claimed in claim 1, further comprising at least one user device coupled to the cable access unit and adapted to receive at least one of communications and data over the network via the cable access unit.
15. (presently cancelled) A system as claimed in claim 14, wherein the at least one user device comprises a phone unit, a television, an answering machine, and a computer.
16. (presently allowed) A method of remotely sensing the power supply states of communication cable access units coupled to a communications network, comprising:
- operably coupling a plurality of communication cable access units to a communication network, the cable access units each coupled to a respective power supply powered by a main power source, and said power supply having a backup battery adapted to supply backup power to an associated cable access unit when the main power source fails;
- monitoring power supply status information from at least one of the cable access units by:

Application No.: 10/047,141

Docket No. BCS03401/PD05970AM

generating a status information signal by the power supply associated with the 1 cable access unit to be monitored indicating at least one of the presence of the backup battery and the power status of the backup battery when the main power fails,

obtaining, at the cable access unit, access information on whether the cable access unit is capable of obtaining the status information on the backup battery, and when so capable, acquiring said status information on the backup battery,

transmitting, from an operator unit to the cable access unit via the network, a request for the access information and status information from the cable access unit for transmission back to the operator unit via said network,

sending the access information back to the operator unit from the cable access unit via the network, and including the status information when the access information indicates the cable access unit is status information collection capable,

processing, at the operator unit, said access information, and also said status information when the access information indicates the cable access unit is status information collection capable, and

displaying an indication of the respective battery status information for an associated cable access unit on a user interface coupled to the operator unit.

17. (presently allowed) A method as claimed in claim 16, further comprising generating status information by the power supply on the backup battery selected from at least one of backup battery on information, backup battery missing information, and backup battery needing replacement information.

18. (presently allowed) A method as claimed in claim 17, further comprising generating by the operator unit an alarm message, including an identification of the associated cable access unit, on the user interface when status information on the backup battery as received from said cable access unit indicates at least one of a backup battery on, a backup battery missing, and a backup battery needing replacement condition for the monitored cable access unit.

19. (presently allowed) A method as claimed in claim 18, further comprising acquiring backup battery status information from a plurality of cable access units located at respective different subscriber premises, and simultaneously displaying, on the user interface, individualized

Application No.: 10/047,141

Docket No. BCS03401/PD05970AM

indications of the respective battery status conditions associated with the respective cable access units.

20. (presently allowed) A method as claimed in claim 19, further comprising maintaining a count of the number of cable access units reporting a backup battery on condition within a predetermined service area.

21. (presently allowed) A method as claimed in claim 20, further comprising displaying a generalized indication on the user interface of a service area wide warning condition in lieu of individualized indications for each cable access unit when the count of the number of cable access units reporting a backup battery on condition within the predetermined service area exceeds a predetermined value.

22. (presently allowed) A method as claimed in claim 16, wherein said acquiring of the status information on the backup battery includes providing a hardware unit detecting and receiving the status information from the power supply, and providing a processor unit checking to determine whether the cable access unit can acquire the backup battery status information via the hardware unit, and when acquired, said processor unit retaining said status information until said request is received at the cable access unit from the operator unit.

23. (presently allowed) A method as claimed in claim 16, wherein said obtaining of status information on the backup battery is performed on a periodic basis.

24. (presently allowed) A method as claimed in claim 16, further comprising at least one user device coupled to the cable access unit and adapted to receive at least one of communications and data over the network via said cable access unit in which the user device is one of a phone unit, a television, an answering machine, and a computer.

25. (presently cancelled) An access unit for use in a communications network comprising:

processing circuitry having a first input, a first output, a second input, and a second output, said processing circuitry first input operably coupled to an operator unit to receive a power supply status query, said processing circuitry first output operably coupled to said operator unit to provide a power supply status thereto; and

a detection unit having a first input coupled to said processing circuitry second output to receive power supply status requests, said detection unit having a second input operably coupled

Application No.: 10/047,141

Docket No. BCS03401/PD05970AM

to a power supply to monitor status of said power supply, said detection unit having a status output coupled to said processing circuitry second input to provide a monitored power supply status thereto.

26. (Presently cancelled) A system for remote sensing of power supply states, said system comprising:

a communications network;

a power supply located at or near a customer's premises, said power supply powered by a power source, said power supply having a backup power supply, said power supply generating one or more power supply status indications;

a cable access unit coupled to said power supply, said cable access unit coupled to said network, said cable access unit powered by said power supply, said cable access unit monitoring one or more of said generated power supply status indications;

an operator unit coupled to said network, said operator unit communicating with said cable access unit to ascertain at least one of said monitored power supply indications; and

a user interface coupled to said operator unit, said operator unit displaying on said user interface an indication of at least one of said ascertained power supply indications,

27. (Presently cancelled) A system as in claim 26, wherein said one or more generated power supply indications is selected from one or more of backup-on, backup-missing, and backup-replace.

28. (Presently cancelled) A system as in claim 27, wherein said communication by said operator unit is carried out in a periodic manner.

29. (Presently cancelled) A system as in claim 28, wherein said periodic communication is carried out by pinging.

30. (Presently cancelled) A system as in claim 29, wherein said backup-on power supply indication is generated in response to said backup power supply providing power to said cable access unit.

Application No.: 10/047,141

Docket No. BCS03401/PD05970AM

31. (Presently cancelled) A system as in claim 30, wherein said backup-missing power supply indication is generated in response to said power supply no longer being coupled to said backup power supply.

32. (Presently cancelled) A system as in claim 31, wherein said backup-replace power supply indication is generated in response to said battery backup supply being in a non-operational state.

33. (Presently cancelled) A system as in claim 29, wherein said backup-missing power supply indication is generated in response to said power supply no longer being coupled to said backup power supply.

34. (Presently cancelled) A system as in claim 29, wherein said backup-replace power supply indication is generated in response to said battery backup supply being in a non-operational state.

35. (Presently cancelled) A method for remote sensing and display by an operator unit of power supply states of power supplies each having a respective backup power supply, each of said power supplies coupled to a respective cable access unit, each of said cable access units coupled to said operator unit, said operator unit coupled to a storage location, each of said power supplies powered by a respective power source, said method comprising:

a) generating, by at least one of said power supplies, a respective power supply status in response to the occurrence of at least one predetermined condition associated with said respective backup power supply;

b) monitoring, by at least one of said cable access units, the power supply status of the respective power supply;

c) reading from said storage location, by said operator unit, identifiers of at least one alarm condition and addresses of at least one of said cable access units to be monitored;

d) communicating with said one or more cable access units by said operator unit to ascertain the power supply status of said respective power supplies;

e) analyzing one or more of said communicated power supply statuses to determine whether any alarm conditions have been generated by said power supplies; and

Application No.: 10/047,141

Docket No. BCS03401/PD05970AM

f) displaying by said operator unit, responsive to said analyzing indicating at least one alarm conditions have been generated, an indication of at least one alarm conditions and the respective generating power supply on a user interface associated with said operator unit.

36. (Presently cancelled) A method as in claim 35, wherein said at least one predetermined condition includes the condition where said backup power supply is supplying power to said respective cable access unit.

37. (Presently cancelled) A method as in claim 35, wherein said at least one predetermined condition includes the condition where said backup power supply is determined to be disconnected from said respective power supply.

38. (Presently cancelled) A method as in claim 35, wherein said at least one predetermined condition includes the condition where said backup power supply is determined to need replacement.

39. (Presently cancelled) A method as in claim 35, wherein said step (d) of communicating comprises the steps of:

i) pinging, by said operator unit, said at least one cable access units, and

ii) receiving, by said operator unit, a response indicating whether any of said at least one alarm condition have been generated.

40. (Presently cancelled) A method as in claim 39, wherein said at least one predetermined condition includes the condition where said backup power supply is supplying power to said respective cable access unit

41. (Presently cancelled) A method as in claim 39, wherein said at least one predetermined condition includes the condition where said backup power supply is determined to be disconnected from said respective power supply.

42. (Presently cancelled) A method as in claim 39, wherein said at least one predetermined condition includes the condition where said backup power supply is determined to need replacement.

43. (Presently cancelled) A computer program product for providing an indication on a user interface of alarm conditions of power supplies, said power supplies each having a backup power supply, said power supplies each coupled to a cable access unit, said cable access units



Application No.: 10/047,141

Docket No. BCS03401/PD05970AM

coupled to an operator unit, said operator unit coupled to said user interface, said computer program product comprising a computer usable medium having a computer readable code thereon, said computer readable program code comprising:

computer readable program code means for generating, by one or more of said power supplies, alarm conditions in respective alarm locations when respective predetermined events occur;

computer readable program code means for monitoring, by one or more of said cable access units, respective ones of said power supplies to determine whether any said alarm conditions have been generated;

computer readable program code means for reading from a storage location, by said operator unit, identifiers of one or more said cable access units;

computer readable program code means for communicating with said identified cable access units by said operator unit to determine whether any of said identified cable access units indicate any of said alarm conditions have been generated; and

computer readable program code means for displaying by said operator unit, responsive to said communication, indications of said any generated alarm conditions and corresponding indicating said identified cable access unit on a user interface associated with said operator unit.

44. (Presently cancelled) A computer program product as in claim 43, wherein said computer readable program code means for monitoring comprises:

computer readable program code means for pinging, by said operator unit, said cable access unit, and

computer readable program code means for receiving, by said operator unit, a response indicating said alarm condition has been generated.

45. (Presently cancelled) A computer program product as in claim 44, wherein said computer readable program code means for generating comprises:

computer readable program code means for determining, by said power supply, whether said power supply is receiving power from said customer power supply, and

Application No.: 10/047,141

Docket No. BCS03401/PD05970AM

computer readable program code means for asserting, by said power supply, a first alarm condition by generating a first signal at a first location in response to said determination indicating said power supply is not receiving power from said customer power supply.

46. (Presently cancelled) A computer program product as in claim 44, wherein said computer readable program code means for generating comprises:

computer readable program code means for determining, by said power supply, whether said power supply is uncoupled from said battery backup supply, and

computer readable program code means for asserting, by said power supply, a second alarm condition by generating a second signal at a second location in response to said determination indicating said power supply is not coupled to said battery backup supply.

47. (Presently cancelled) A computer program product as in claim 44, wherein said computer readable program code means for generating comprises:

computer readable program code means for determining, by said power supply, whether said battery backup supply is non-operational, and

computer readable program code means for asserting, by said power supply, a third alarm condition by generating a third signal at a third location in response to said determination indicating said power supply is not receiving power from said customer power supply.

48. (Presently cancelled) An operator unit for use in a network comprising:

a control query output adapted to be operably coupled to one or more access units in said network, said control query output to provide power supply status queries to said one or more access units;

an analyzation unit having a status reply input adapted to be operably coupled to said one or more access units, said status reply input to receive power supply status reply messages from said one or more access units, said analyzation unit having an output to provide notice of any asserted alarm conditions; and

an operator interface having an input coupled to said analyzation unit output; said operator interface having an output to provide an alarm condition warning.

Application No.: 10/047,141

Docket No. BCS03401/PD05970AM

49. (Presently cancelled) An operator unit as in claim 48, wherein said operator interface output is one or more of a visual display, a speaker, and a tactile feedback device.

50. (Presently cancelled) An operator unit as in claim 49, said operator unit further comprising:  
a counting unit having an input coupled to said analyzation unit output and an output to provide at least a partial count of the number of access units asserting an alarm condition, said operator interface having a count input coupled to said counting unit output, said operator interface warning output to provide at least one of an individual alarm condition warning and a multiple-access unit alarm condition warning.

51. (Presently cancelled) An operator unit as in claim 49 said operator unit further comprising:  
a counting unit having an input coupled to said analyzation unit output and an output to provide at least a partial count of the number of access units asserting an alarm condition a gauge unit having an input coupled to said counting unit output and an output to provide a service-area wide alarm condition warning when said count equals or exceeds a predetermined count threshold, said gauge unit output coupled to said operator unit input, said operator interface warning output to provide at least one of an individual alarm condition warning and a multiple-access unit alarm condition warning.

52. (Presently cancelled) An operator unit as in claim 49, wherein said alarm condition warning includes an identification of the associated access unit and at least one of a battery-on, a battery-missing, and a battery-failed alarm condition.